



## Product Information Sheet

### ATF Dexron III-H/Mercon **AUTOMATIC TRANSMISSION FLUID**

#### **General Description:**

FLOMAX ATF Dexron III-H meets the special frictional characteristics, transmission cleanliness and low temperature pumpability required by the Dexron III-H and Mercon specifications of General Motors and Ford, respectively.

Careful base oil selection assures excellent low temperature performance for ATF Dexron III-H Mercon while the specialized performance additive provides superior oxidation resistance for extended use under high temperature operating conditions and smooth power transfer during shift cycles. ATF Dexron III-H Mercon contains special additives to prevent oil seal deterioration while providing superior resistance to foaming. The superb frictional properties of ATF Dexron III-H, Mercon, which affect the feel of shifting, are retained for an extended period of time.

There is an increasing trend toward manufacturers using ATF (Automatic Transmission Fluid) for hydraulic applications, especially in cold weather environments. The superior anti-wear performance built into AFT Dexron III-H, Mercon assures proper protection of these hydraulic pumps and systems for the applications

where Dexron, Dexron II, or Dexron III fluids are recommended.

#### **Features and Benefits:**

**Frictional Properties:** Outstanding frictional characteristics provide smooth shifting and excellent retention of shifting performance throughout the service interval.

#### **Manufacturers' Performance:**

Dexron III-H, Mercon has performance level additives for OEM transmission manufacturers applications.

#### **High Temperature Protection:**

Excellent oxidation and sludge protection for high transmission temperatures experienced by modern cars.

**Cold Flow:** Superior cold temperature flow characteristics assures ease of pumping and good shifting capabilities, even at extremely low temperatures.

**Typical Application:** Is suitable for use in all applications where manufacturers recommend:

- Dexron III-H, G
- Dexron IIE
- Dexron II
- Dexron
- Type A, Suffix A
- Mercon
- Ford M2C-138CJ
- Ford M2C-166H
- Ford Type H
- Allison C-4

## **ATF Dexron III-H Mercon AUTOMATIC TRANSMISSION FLUID**

### **Typical Customer**

Owners and operators of:

- Most General Motors and Ford brands of automobiles and light trucks
- Selected hydraulic systems

### **Health & Safety**

A complete Material Safety Data Sheet is available upon request. Used oil may be harmful, avoid prolonged or repeated skin contact. Wash clothing and exposed areas with soap and water. Don't pollute – return used oil to a collection center.

### **Typical Properties**

<b>Qualifications:</b>	<b>Dexron III-H Mercon</b>
Viscosity, cSt	
@ 40 Deg. C.	34.4
@ 100 Deg. C	7.1
Viscosity Index	163
API Gravity	32.8
Pour Point, Deg. F	<-60
Flash Point, Deg. F	417
Color	RED

